

SAS-S/SAS-M

SINGLE ANIMAL SCALE



RICE LAKE[®]
WEIGHING SYSTEMS

800-472-6703
www.ricelake.com

SAS-S/SAS-M

SINGLE ANIMAL SCALE



Single Animal Weighing Anywhere You Need It

The SAS offers safe and reliable weighing for a wide range of livestock including cattle, horses, sheep, swine and exotics. With a load capacity of up to 5,000 pounds and Legal for Trade readability in one pound increments, the SAS is ideal for county fairs, youth agriculture organizations, university research centers, veterinary practices and producers with fewer than 500 head annually.

Stationary or Mobile

The SAS is available in a stationary (SAS-S) or mobile configuration with a mobile transport device (SAS-M). The mobile transport device can be installed as an aftermarket attachment to existing SAS-S scales, allowing stationary scales to become mobile. If the mobile transport device is purchased, the SAS-M with 920i® Rate of Gain weigh center can be relocated without the need to recalibrate.

Solid Construction

The SAS is built with 48-inch solid kick panel sides and thick wall tubing for added operator and animal safety. The subframe features a durable, 3 x 6 inch thick wall tubing. A choice from swing gates, sliding gates or combination gates ensures the best fit for the environment's demands. Gates are also interchangeable after use, allowing the scale to change with your operations. Load cells and electronic components are housed in protective enclosures above the subframe, away from muddy and sloppy ground.

Flooring

The SAS features unmatched traction for animals in wet and slippery conditions with a choice of either X-Lug or X-Plank flooring. Both styles are made from durable, recycled plastic and rubber material that will never rot or harbor bacteria. X-Lug flooring uses a deep, aggressive tread, and X-Plank flooring utilizes a less-aggressive, wheel-accessible tread.



X-Plank flooring



X-Lug flooring

Your Rice Lake Weighing Systems distributor is:

920i Rate of Gain Weigh Center for SAS-M

The weigh center is mounted on the exterior of the cage for easy operation and viewing. A legal ticket can be printed and the weatherproof enclosure protects instrumentation. RATTLETRAP® digital filtering ensures stable weights even when animals are moving on the scale. The 920i Rate of Gain digital weight indicator software is the perfect addition to an SAS-M system. The software allows ID tag entry either manually or with an Allflex® RS420 Series wand. The software tracks rate of gain by date and provides average rate of gain per day when two to three weights are entered for the same ID number.

Standard Features

- Inside Dimensions: 8 x 3 ft
- Swing gate, sliding gate or combination
- 48 in solid kick panel sides
- Ships fully assembled
- Mobile or stationary configurations

Options/Accessories

- Instrumentation enclosure
- Ticket printer
- RS-420 portable tag reader
- 920i single animal Rate of Gain for stationary unit (SAS-S)
- 920i single animal Rate of Gain for mobile unit (SAS-M)
- AC/DC powered indicators

Specifications

Capacity:	5,000lb load cell
Warranty:	Two-year limited warranty
Approvals:	NTEP CC 99-091 Measurement Canada AM4847

Approvals



Measurement
Canada
Approved

RICE LAKE
WEIGHING SYSTEMS

230 W. Coleman St. • Rice Lake, WI 54868 • USA
TEL: 715-234-9171 • FAX: 715-234-6967 • www.ricelake.com

An ISO 9001 registered company © 2015 Rice Lake Weighing Systems PN 173717 12/15
Specifications subject to change without notice.